

Ecoguss drain body DN 100, Horizontal outlet



Article information

Item no.: 48311

GTIN: 4026092033272

Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125

Waterproofing layer on the drain body: Connection flange

Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1 Nominal size (DN): 100 Outer diameter (OD): 110 mm

Dimensions

Net weight:1,05 kgGross weight:1,16 kgDiameter:135 mmHeight:132 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height



Tank/drain body

Number of outlets: 1

Material of drain body: Ecoguss System: lateral

Coverage features

Odour trap: included