

## Shell Kit Aqualift S Compact tileable GTF500 Duo



### Article information

Item no.: 280510X-RBK

GTIN: 4026092106938

Price group: 20

### Description

For combination with a KESSEL technology kit for creating a Duo lifting station for wastewater without sewage with a GTF500 wastewater pump. The ready to plug in lifting station for wastewater without sewage is equipped with a submersible pump and a backflow preventer. The collection tank made of permanently resistant polymer (PE) has an open pump tank. One-handed closures enable easy removal of the integrated components. The system for installation in the floor slab is pre-assembled for final installation on site. KESSEL shell kit consisting of:

- With vertically adjustable upper section for continuous height and level compensation and integrated floor drain - PE collection tank, resistant to aggressive wastewater and 3 m groundwater - Includes backflow preventer for the pressure pipe - Includes connection socket for inlet and conduit pipe

#### Variant

Type of system:

duo pump

Rim width:

Float switch

#### General characteristics

Colour:

black

Standard:

EN 12050-2

Type of wastewater:

without sewage

Installation situation:

floor slab installation

Delivery state:

Installation-ready (connection parts must be connected on site)

#### Dimensions

Net weight:

16,2 kg

Gross weight:

16,2 kg

Groundwater resistant from lower edge of base section:

3000 mm

Installation depth:

490 - 620 mm

Vertical adjustment:

vertically adjustable upper section

Length:	617 mm
Width:	585 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Pressure pipe connection (DN):	32
Pressure pipe connection (OD):	40 mm
Inlet nominal size (DN):	100 mm
Pumping volume:	16 l
Tank volume:	65 l
Coverage features	
Type of cover:	tileable cover plate
Cover material:	Polymer
Colour of cover:	grey
Width of cover:	366 mm
Length of cover:	366 mm
Drainage function:	yes
Cover locking:	Lock & Lift
Load class:	K 3 (EN 1253-1)
Max. flooring height:	16 mm
Pumping device	
Pump control:	GTF 500
Number of pumps:	2
Max. pumping height:	8 m