

Practicus drain body Press. fl., DN 100, Vertical outlet



Article information

Item no.: 45219

GTIN: 4026092033821

Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Variant

System: 125

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Waterproofing layer on the drain body: Press sealing flange (suitable for creating

watertight seals)

Sealing water height: 50 mm

General characteristics

Nominal size (DN): 100 Outer diameter (OD): 110 mm

Inlet max. scoring (DN): Z-19.53-2414,Z-19.17-1719

Dimensions

Net weight:1,9 kgGross weight:2,22 kgDiameter:273 mmHeight:217 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets: 1



PP Material of drain body:

System: vertical

Coverage features

Odour trap: included