



Ecoguss project drain DN 80, vert., Variofix, Slotted cover





Article information

Item no.: 48483.51 GTIN: 4026092034392

Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss project drain with connection flange is used for point drainage and is equipped with a removable odour trap as well as a lip seal and a temporary protective cover. The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Variant

System: 125

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Waterproofing layer on the drain body: Connection flange

Sealing water height: 50 mm

General characteristics

Standard: EN 1253-1 Nominal size (DN): 80 Outer diameter (OD): 83 mm

Inlet max. scoring (DN): Z-19.53-2414,Z-19.17-1719

Dimensions

Net weight: 2,54 kg
Gross weight: 2,82 kg
Diameter: 135 mm



Vertical adjustment: vertically adjustable upper section

Length:135 mmWidth:135 mmPackaging dimension:lengthPackaging dimension:widthPackaging dimension:height

Tank/drain body

Number of outlets: 1

Material of drain body: Ecoguss System: vertical

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover:silverWidth of cover:138 mmLength of cover:138 mmMin. flooring height:10 mm

Surface: Polished SST

Frame material: Stainless steel 14301

Cover locking: screwed

Load class: K 3 (EN 1253-1)

Rim length: 150 mm
Rim material: 150 mm
Max. flooring height: 17 mm

Upper section: adjustable in three dimensions

Shape of upper section: square
Upper section material: ABS
Odour trap: included